

Document made available under the Patent Cooperation Treaty (PCT)

International application number: PCT/US05/028526

International filing date: 10 August 2005 (10.08.2005)

Document type: Certified copy of priority document

Document details: Country/Office: US
Number: 60/599,872
Filing date: 10 August 2004 (10.08.2004)

Date of receipt at the International Bureau: 03 October 2005 (03.10.2005)

Remark: Priority document submitted or transmitted to the International Bureau in compliance with Rule 17.1(a) or (b)



World Intellectual Property Organization (WIPO) - Geneva, Switzerland
Organisation Mondiale de la Propriété Intellectuelle (OMPI) - Genève, Suisse

1371805

THE UNITED STATES OF AMERICA

TO ALL TO WHOM THESE PRESENTS SHALL COME:

UNITED STATES DEPARTMENT OF COMMERCE

United States Patent and Trademark Office

September 22, 2005

THIS IS TO CERTIFY THAT ANNEXED HERETO IS A TRUE COPY FROM THE RECORDS OF THE UNITED STATES PATENT AND TRADEMARK OFFICE OF THOSE PAPERS OF THE BELOW IDENTIFIED PATENT APPLICATION THAT MET THE REQUIREMENTS TO BE GRANTED A FILING DATE.

APPLICATION NUMBER: 60/599,872

FILING DATE: August 10, 2004

RELATED PCT APPLICATION NUMBER: PCT/US05/28526



Certified by

Under Secretary of Commerce
for Intellectual Property
and Director of the United States
Patent and Trademark Office

Please type a plus sign (+) inside this box →



Revised PTO/SB/16 (8-00)
Approved for use through 10/31/2002. OMB 0651-0032
Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.
Attorney Docket No. 29953-206699

PROVISIONAL APPLICATION FOR PATENT COVER SHEET

This is a request for filing a PROVISIONAL APPLICATION FOR PATENT under 37 CFR 1.53 (c).

INVENTOR(S)					
Given Name (first and middle [if any])	Family Name or Surname	Residence (City and either State or Foreign Country)			
Garrett	Pennington	York, PA			
<input type="checkbox"/> Additional inventors are being named on the _____ separately numbered sheets attached hereto					
TITLE OF THE INVENTION (280 characters max)					
INDUCTION SEALING HEAT PROFILE IMPROVEMENT					
CORRESPONDENCE ADDRESS					
Direct all correspondence to:		<div style="border: 1px solid black; padding: 5px; text-align: center;">*26694* 26694 PATENT TRADEMARK OFFICE</div>			
<input checked="" type="checkbox"/> Customer Number		26694		→	
OR Type Customer Number here					
<input checked="" type="checkbox"/> Firm or Individual Name	VENABLE LLP				
Address	P.O. Box 34385				
Address					
City	Washington	State	DC	ZIP	20043-9998
Country	U.S.A.	Telephone	202.344.4000	Fax	202.344.8300
ENCLOSED APPLICATION PARTS (check all that apply)					
<input checked="" type="checkbox"/> Specification Number of Pages		6		<input type="checkbox"/> CD(s), Number	
<input type="checkbox"/> Drawing(s) Number of Sheets		5		<input type="checkbox"/> Other (specify)	
<input checked="" type="checkbox"/> Application Data Sheet. See 37 CFR 1.76					
METHOD OF PAYMENT OF FILING FEES FOR THIS PROVISIONAL APPLICATION FOR PATENT (check one)					
<input type="checkbox"/> Applicant claims small entity status. See 37 CFR 1.27.				FILING FEE AMOUNT (\$)	
<input type="checkbox"/> A check or money order is enclosed to cover the filing fees					
<input checked="" type="checkbox"/> The Commissioner is hereby authorized to charge filing fees or credit any overpayment to Deposit Account Number:				22-0261	
<input type="checkbox"/> Payment by credit card. Form PTO-2038 is attached.				160.00	
The invention was made by an agency of the United States Government or under a contract with an agency of the United States Government.					
<input checked="" type="checkbox"/> No.					
<input type="checkbox"/> Yes, the name of the U.S. Government agency and the Government contract number are: _____					

Respectfully submitted

SIGNATURE

TYPED or PRINTED NAME James R. Burdett

TELEPHONE 202-344-4000

Date

8/10/2004

REGISTRATION NO.
(if appropriate)

31,594

Docket Number:

29953-206699

USE ONLY FOR FILING A PROVISIONAL APPLICATION FOR PATENT

This collection of information is required by 37 CFR 1.51, and is used by the public to file (and by the PTO to process) a provisional application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. SEND TO: Box Provisional Application, Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

22151 U.S. PTO
60/599872



081004

PATENT PROSECUTION FILING RECEIPT

121594

Venable Filing Number

Atty. Docket No: 29953-206699

Title of Application: Induction Sealing Heat Profile Improvement

Application No: N/A

Patent No.:

Attorney/LAA:

JRB:lrh

PTO Due Date:

August 10, 2004

Current Date:

August 10, 2004

Filing Date:

August 10, 2004

Issue Date:

The following items were received from Venable, Washington, D.C., by the U.S. Patent & Trademark Office:

U.S. PTO FEES ENCLOSED

- ☒ Transmittal Letter
- ☐ Fee Transmittal Letter
- ☒ New U.S. Provisional Application (specification/claims)
- ☐ Rule 53(d) Continued Prosecution Application
- ☐ Rule 53(b) Continuation or Divisional Application (**attach copy of specification, claims, drawings and declaration**)
- ☐ U.S. National Stage Application of PCT Application
- ☐ Request for Continued Examination (RCE) under 37 CFR 1.114
- ☐ Request for Reconsideration
- ☐ Substitute Specification
- ☐ Priority Document-Cert. Copy of Appln.#: ; Country
- ☐ Date Filed:
- ☐ Formal Drawings (sheets, Figs.)
- ☐ Invention Declaration
- ☐ Assignment w/Cover Sheet
- ☐ Response to Notice to File Missing Parts
- ☐ Response to Notice to File Missing Requirements
- ☐ Response to Restriction Requirement
- ☐ Response
- ☐ ☐ Amendment/☐ Preliminary Amendment
- ☐ Petition/Request for Extension of Time (mo. ext.)
- ☐ Power of Attorney
- ☐ Petition to Revive
- ☐ Sequence Listing – CDR Enclosed? ☐ Yes ☐ No
- ☐ Request for Non-Publication
- ☐ Request to Rescind Non-Publication Request
- ☐ Terminal Disclaimer
- ☐ Notice of Appeal
- ☐ Appeal Brief (**in triplicate**)
- ☐ ☐ Reply Brief (**in triplicate**)/ ☐ Request for Oral Hearing
- ☐ Confirmation of Hearing Petition
- ☐ Issue Fee Transmittal
- ☐ Certificate of Correction
- ☐ Maintenance Fee Transmittal
- ☐ Status Inquiry
- ☐ Other: (**Please describe below**)

Filing Fee

Surcharge Fee

Additional Claim Fee
Recordation/Indexing
Fee

IDS Fee

Extension Fee

Notice of Appeal Fee

Brief on Appeal
Oral Hearing Request
Fee

Petition Fee

Issue Fee

Publication Fee

Maintenance Fee

Other Fees (Describe)

Total Fees Paid

☐ Check Number

Attached

☒ Charge Deposit Account No.
22-0261*

*If the Deposit Account was
used, was a copy of this form
sent to Accounting?

☒ Yes ☐ No

Cap Closure With Improved Induction Heated Seal**FIELD OF THE INVENTION**

[0001] This invention relates generally to a bottle having a cap closure with an induction heated seal. More particularly, the invention is related to a blow molded bottle or container that has an improved induction heated seal.

BACKGROUND OF THE INVENTION

[0002] Leaking between the cap and the bottle is a common problem with extrusion blow molded bottles where neck finish tolerances can vary by as much as +/- 0.3 mm. Various types of caps have been developed, especially for use by the dairy industry, where leaking bottles can be a major problem for fillers, retailers and consumers. However, none of the developments so far seem to solve the problem, which is inherent in the lightweight extrusion blow molded neck finish.

[0003] Conventionally, milk has been packaged in cardboard, gable top packs, which are notoriously difficult to open and result in numerous consumer complaints about milk spillage and difficulty in pouring. The fiber carton was only suitable for packaging liquids up to a capacity of 1.5 liters.

[0004] In order to resolve these problems blow molded plastics polyethylene bottles have been used. These bottles are provided with resealable caps. The resealable caps are normally injection-molded items. Since weight is significant in the packaging of fluids such as milk, these caps must also be light in weight. A weight of 2 to 4 g is usually the maximum that can be tolerated.

[0005] There is also a fundamental problem in achieving a good seal between a blow molded bottle neck and an injection molded plastics cap. This is because the tolerance of the neck is of the order of 0.3mm whereas the tolerance of an injection-molded item such as the cap is 0.1mm. This means that a proportion of caps will not seal tightly when fitted to their necks. For all designs of caps this results in difficulties of fitting on the production line and, for retailers and distributors, leakage problems. The ultimate consumer may also have difficulty in resealing the bottle or opening it in the first place if the cap is over-tight.

[0006] A number of designs of injection molded caps have been developed in an attempt to address these problems. For example, in a cap design known as a valve seal or pliable seal closure, a plug is provided in the cap which pushes into the neck of the bottle and a

multiple start thread is provided on the interior wall of the cap skirt. This type of cap provides a double seal. The plug provides the seal against the inner wall of the neck. The second seal is provided by means of an inwardly projecting ridge above the threads on the inner wall of the cap, which seals against the outer wall of the neck. A pliable pull away ring around the lower edge of the cap can provide tamper evidence for this type of cap. With a cap made of low density polyethylene, it is possible to prise off the cap with the ring attached so that this form of tamper evidence is not very secure.

[0007] Another design known as the induction heat seal closure (IHS) provides a foil insert seated into the base of the cap. On the production line the filled bottles with caps fitted are passed through an induction heater, which fuses the foil to the neck of the bottle. When the consumer unscrews the cap the neck of the bottle is still sealed by the foil. This foil seal is pulled off in a separate operation. Severing the seal results in small hairs of the plastics material being raised on the surface of the bottle neck which can inhibit a good seal being formed when the cap is replaced after initial opening. The setting of parameters for the bonding process using an induction heat seal closure is critical in order to achieve a bond which is weak enough to allow the consumer to be able to peel away the foil, yet strong enough to maintain a good primary seal with the container neck. Because the presence of the foil means that no plug can be provided the susceptibility to leakage in the consumer's home is increased as the resealing of the cap is poor. The cap is also relatively expensive as the provision of the peelable foil insert can add as much as 20% to the cost of the container.

[0008] More recently, Spreckelsen McGeough of Little Gawton, Horsell Vale, Woking, Surrey GU21 4QU Great Britain, has taken a fresh approach to this old problem. The result is a bonded aluminum plastic (or BAP[®], a registered trademark of Spreckelsen McGeough) closures, which comprise a cap, foil seal and bottle neck all in one, that is welded to the HDPE bottle after filling.

[0009] The BAP closure consists of a cap and a precision injection molded bottle neck with a pourer lip. The lower end of the neck is sealed with an induction welded aluminum foil which itself includes an integrated pull ring. The snap-on cap is supplied already fitted to the bottle neck. Immediately after filling the BAP closure is placed on top of the bottle and the lower surface of the foil is welded to the open bottle neck. This results in a highly effective seal between the bottle and the BAP closure, which are in effect welded to either face of the

aluminum foil. When the cap is removed the consumer opens the container by simply tearing out the central area of the aluminum foil using the integrated pull-ring, and discards it. The remaining narrow annular section of foil continues to perform its role in welding together the two parts of the bottle. The bottle can be successfully resealed using the snap-on cap only. By using an injection-molded neck finish and an injection-molded cap a high quality secondary seal is easily achievable.

[0010] Tests carried out by Spreckelsen McGeough indicate that the seal achieved is far superior to that achieved using a conventional valve cap or foil cap.

[0011] The role of the BAP closure in reducing leakage in extrusion blow molded bottles is clear, but there are other, less obvious advantages. For the bottler there is a considerable saving on material, with the ability to use even lower bottle weights. The fact that the bottle neck is fitted after filling totally divorces the neck finish from the filling aperture – in other words a much larger diameter filling aperture can be designed into the bottle, regardless of the selected cap size, increasing filling speeds and enabling bottlers to increase output from existing equipment. The designers claim that these features alone more than compensate for the additional cost of the BAP closure.

[0012] A disadvantage of many foil seals is the difficulty in removing them, either because they are too firmly welded to the bottle or because the pull-tab is too small to grip. The BAP pull-ring foil provides tamper evidence as well eliminating this problem. And the precision molded lip makes it easy to pour, even from a lightweight 3 or 5 liter bottle of milk.

[0013] Because PET neck finishes are injection molded they do not present the leakage problem seen in HDPE, but BAP technology also has potential applications in aseptic filling, retort sterilization filling and other areas. The cap closure with improved induction heated seal according to the present invention is particularly useful with wide-mouth, blown finishes.

[0014] Further objectives and advantages, as well as the structure and function of preferred embodiments will become apparent from a consideration of the description, drawings, and examples.

BRIEF DESCRIPTION OF THE FIGURES

[0015] The foregoing and other features and advantages of the invention will be apparent from the following, more particular description of a preferred embodiment of the invention, as

illustrated in the accompanying drawings wherein like reference numbers generally indicate identical, functionally similar, and/or structurally similar elements.

[0016] Figure 1

[0017] Figure 2 shows the average temperature of the foil for the current induction coil design;

[0018] Figure 3 shows the max temperature of the foil for the current induction coil design;

[0019] Figure 4 shows the foil when it was sealed with the regular induction sealing head;

[0020] Figure 5 shows the foil being sealed with metal placed in the center of the object; and

[0021] Figure 6 shows a digital image of the BAP closure with the foil induction sealed to it.

DETAILED DESCRIPTION OF THE INVENTION

[0022] Embodiments of the invention are discussed in detail below. In describing exemplary embodiments, specific terminology is employed for the sake of clarity. However, the invention is not intended to be limited to the specific terminology so selected. While exemplary embodiments are discussed, it should be understood that this is done for illustration purposes only. A person skilled in the relevant art will recognize that other components and configurations can be used without parting from the spirit and scope of the invention. All references cited herein are incorporated by reference as if each had been individually incorporated.

[0023] The present invention consists of a new induction sealing head design that solves current 63+ mm BAP closure ring pull failures. These ring pull failures are due to the input of excess heat into heat sensitive bonded areas. This invention will allow the outer edge of the sealing foil to reach an appropriate sealing temperate while preventing the interior foil temperature from heating beyond ring pull bond failure.

[0024] The present invention will also have the ability to reduce the amount of heat that goes into the product but still maintain the proper amount of heat that is required for generating a proper seal. By reducing the amount of heat going into the product, the customer has less of a chance for obtain a burned smelling or tasting product.

[0025] The old method consists of a coil which will generate a magnetic field when a large voltage is supplied to the coil. This magnetic field is then absorbed into the aluminum foil which causes it to heat up. Since the foil has a layer of plastic on the foil, the plastic also heats.

[0026] The disadvantages of this system is that the operator must have the system set to a level that provides an adequate seal but does not exceed that temperature or the foil will burn and cause the product to smell/taste burnt. Although this balance has been obtained in the current industry it has not been obtained for the BAP closure systems. The BAP closure has an aluminum foil with a layer of plastic on each side of the foil. When the foil is heated it melts the plastic and will become bonded to the interfacing parts (cap and bottle). The problem that arises is that when a cap has a lower melting point then the bottle (the plastic on the foils have two different melting points), the lower melting point will be reached and will loose its bond strength while attempting to bond the higher melting point temperature.

[0027] The novelty of the present invention is that it places a metal object which would be cooled fluidly inside the induction coil head. This object, which could be a tube or machined cooling line, will absorb the induction field currents (since it is metal) in areas that the foil should not heat up and then the heat would be removed from the part by the cooling system. The advantage is that this invention may prevent the failure of the BAP closures when being sealed onto a PET package. It will also remove the heat going into the product which will prevent consumers from obtaining burnt smelling or tasting products.

[0028] The present invention takes an induction coil head (the current ideas have been considered for a round coil configuration but this may be able to be implemented on linear line induction systems) and implement it in either of the following configurations: 1) a copper tube, or machined metal piece will be placed in the induction head between the induction coil and the cooling lines will exit through the top of the coil; or 2) a metallic plate will with the corresponding cooling lines will be mounted to the base of the induction coil.

[0029] As shown in the figures, a temperature profile of the different power settings and the duration of time that the corresponding power setting was applied according to the present invention. These two graphs shown in Figures 2 and 3 the average temperature of the foil and also the max temperature of the foil for the current induction coil design.

[0030] Also shown are the average and maximum temperature for the regular induction sealing head. This graph also shows the average and maximum temperatures that were obtained

for a time: 4 sec and power: 6. The difference in the graph shows that a metal insert will reduce the average temperature.

[0031] By placing a metallic object or any material that will absorb the induction field, we can control the temperature in the center of the foil. Other areas of the foil could also be controlled but we are currently focusing on the center. The maximum temperature for the presently preferred embodiment (polypropylene closure to a PET package) must be at the outer edge of the foil, which is where the PET package makes contact. The present invention is focused currently on the PET material since it has a higher melting point temperature (approximately 550°F) than the polypropylene (approximately 260°F).

[0032] Figures 4 and 5 show the temperature profile of the foil at when it achieves the maximum point in the sealing process. Figure 4 shows the foil when it was sealed with the regular induction sealing head. Figure 5 image shows the foil being sealed with metal placed in the center of the object. As one can readily appreciate from the max and min temperatures on the Figures 4 and 5, the present invention can lower the temperature where the metal resides.

[0033] Figure 6 shows a digital image of the BAP closure with the foil induction sealed to it.

[0034] The embodiments illustrated and discussed in the specification are intended only to teach those skilled in the art the best way known to the inventors to make and use the invention. Nothing in this specification should be considered as limiting the scope of the present invention. All examples presented are representative and non-limiting. The above-described embodiments of the invention may be modified or varied, without departing from the invention, as appreciated by those skilled in the art in light of the above teachings. It is therefore to be understood that, within the scope of the claims and their equivalents, the invention may be practiced otherwise than as specifically described.

63mm BAP Foil Temperature




Fig. 1




Fig. 2

Max Foil Temperature




Fig. 3




Fig. 4




Fig. 5




Fig. 6

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☒ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.

APPLICATION DATA SHEET

Application Information

Application Number::

Filing Date:: Concurrently

Application Type:: Regular

Subject Matter:: Utility

Suggested Classification::

Suggested Group Art Unit::

CD-ROM or CD-R?::

Number of CD Disks::

Number of Copies of CDs::

Sequence Submission?::

**Computer Readable Form
(CFR)?::**

Number of Copies of CFR::

Title:: Induction Sealing Heat Profile Improvement

Attorney Docket Number:: 29953-206699

Request for Early Publication?::

Request for Non-Publication?::

Suggested Drawing Figure::

Total Drawing Sheets::

Small Entity?:: NO

Latin Name::

Variety Denomination Name::

Petition Included?::

Petition Type::

Licensed US Govt. Agency::

Contract or Grant Numbers::

Secrecy Order in Parent Appl.::

Applicant Information

Applicant Authority Type:: Inventor
Primary Citizenship:: US
Country:: USA
Status:: Full Capacity
Given Name:: Garrett
Middle Name::
Family Name:: Pennington
Name Suffix::
Country of Residence:: USA
Street of Mailing Address:: 629 S. Hampton at Waterford
City of Mailing Address:: York
Country of Mailing Address:: USA
Postal or Zip Code of Mailing Address:: 17402

Correspondence Information

Correspondence Customer Number:: 26694
Phone Number:: (202) 344-4000
Fax Number:: (202) 344-8300
E-Mail Address::

Representative Information

Representative Customer Number:: 26694

Domestic Priority Information

Application::	Continuity Type::	Parent Application::	Parent Filing Date::
	Continuation of		

Assignee Information

Assignee Name::	Graham Packaging Company
Street of Mailing Address::	2401 Pleasant Valley Road
City of Mailing Address::	York
State or Province of Mailing Address::	PA
Country of Mailing Address::	USA
Postal or Zip Code of Mailing Address::	17402